

PLEASE READ CAUTIONS

- 1. In rare instances, some rubber products may stain the tile's surface. Test by placing a single tile under rubber tires, chair bottoms, coasters etc. for 48 hours prior to installation.
- 2. Check all cartons to ensure they are the **same batch code**. Color variations may occur between batches due to tiles being made from recycled materials.
- 3. Most chemicals will not stain. Pet urine may cause tile to yellow. Remove chemical spills as soon as possible. Petroleum products may cause tile to deteriorate if left unattended.
- 4. To insure easy installation, remove the tiles from the cartons and spread them out on the floor where they can acclimate to room temperature 24 hours prior to installation.
- 5. Tile will need to slide across subfloor as it expands, if laying tile on a rough surfaces like plywood or rough concrete an underlayment of .03 mm (or thicker) plastic will allow the tile to slide as it expands.
- 6. Be sure to leave a 1/4" expansion gap around all edges in wall-to-wall installations.
- 7. Most non-slip vinyl wax or sealer will add to the ease of cleaning. We recommend Armstrong Shine Keeper. Always test waxes or sealer before applying.
- 8. Warranty does not cover dirt or staining of white or lighter colored tiles used in garages, areas exposed to dyes, petroleum products, or similar applications. Urethane Flexi-Coating may be used over white and lighter colors to prevent soiling and staining.
- 9. Never use bleach to clean tiles. Bleach will discolor tile. For sterilizing, use ½ cup of vinegar in a gallon of water.
- 10. This tile is for Interior Use Only and must be installed between 60 and 90 degree tempertures.

